



Funkenerosion

MD 840 CNC

***EDM drilling machine type Micro Drill
with PC control system***



- + electrodes
 \varnothing 0,08 - 3,00 mm
- + travel
800x400
- + Z-axis motor-driven
adjustable and
programmable
- + work piece height
250 mm (opt. 280 mm)
- + 15" touch
screen monitor
- + incl. external tank-
and filter unit
100 l tank capacity

MD 840 CNC - high precision EDM drilling machine

technical data:

machine body

max. work piece dimensions	mm	1180x700x250
travel x y motor driven	mm	800x400
max. work piece weight	kg	600
machine weight	kg	1600
rough adjustment Z-axis	mm	250
controlled W-axis = eroding axis lift	mm	300
for electrode diameter	mm	0,5 - 3,00 (opt. 0,08)
usable electrode length	mm	till 400

generator:

integrated into machine base
input voltage supply fuse FET technic, capacity
max. 5 KVA
3 Ph. 400 Volt / 50 ~ 60 Hz
min. 16 Amp.
40 Amp.

PC control system

operating system Windows 7
ergonomically designed operation terminal
high-resolution 15" color display flat screen
interface USB/LAN

features:

automatic electrode wear compensation
automatic parameter setting
automatic setting of drilling depth
backlash compensation
soft start function
automatic touching functions
interactive programme functions
dry run simulation
realtime self-diagnostic
resolution 0,001 mm (servo motor)
interpolation linear/circular
integrated CAD/CAM Software

single block function
blindhole drilling mode
monitored breakthrough drilling mode
significant monitoring of current drilling

standard accessories:

- 1 set tools and accessories in tool box
- 1 set electrode changing holder Ø 1,00 mm (incl. holder, chuck, seal, plunger)
- 1 pcs. ceramic guide Ø 1,00 mm
- 20 pcs. brass electrodes Ø 1,00 mm